

IN THE SPECIFICATION:

Please amend the specification as follows:

At page 5, lines 19-23, please change "Figure 4 is a schematic top plan view of a plurality of toilets, a, b, c, d and e, illustrating different toilet bowl openings into which the improved drain plunger of the present invention can fit;" to, --Figure 4 is a schematic side view elevation, of a preferred embodiment of the toilet and sink drain plunger of the present invention showing the plunger with an integrally formed handle.--

At page 10, lines 5-8, please replace "Fig. 4 shows an array of different toilet bowls, 64, 66, 68, 70 and 72 in respectively (a), (b), (c), (d), and (e), all of which can be effectively sealed and unclogged by plunger 10.", with --Plunger 10 can fit into a many different toilet bowl openings. Hence, a variety of different toilet bowls can be effectively sealed and unclogged by this plunger 10.--

At page 5, line 28, please delete "Figure 6 is a schematic side view elevation, of a preferred embodiment of the toilet and sink drain plunger of the present invention showing the plunger with an integrally formed handle."

At page 6, after line 20, please change, "Alternately the entire plunger 10 can be of unitary construction, as shown in FIG. 6.", to "Alternately the entire plunger 10 can be of unitary construction, as shown in FIG. 4."

IN THE DRAWINGS:

Please replace FIG. 4 with new FIG. 4.